

屋内照明器具特性	
品番 (品名)	NYM20245 + NYK00112
光源	LED5000_85_38070 ×1 38070.0 lm
管理番号	K0185707 (0) DB 1
BZ分類	BZ1 / 0.9 / BZ2 / 4.5 / BZ3

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	4 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	96 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.77	0.6	72	63	57	53	70	62	57	53	68	61	56	53	66	60	56	52	51
		0.72	0.8	79	71	66	62	78	70	65	61	75	69	64	61	73	67	63	60	58
		0.68	1.0	84	77	71	67	83	76	71	67	80	74	70	66	77	72	69	66	63
			1.25	88	82	77	73	87	81	76	72	84	79	75	71	81	77	73	70	68
下方投影面積	c m ²	1.5	91	85	80	77	90	84	80	76	87	82	78	75	84	80	77	74	71	
		2.0	95	90	86	82	93	89	85	82	90	86	83	80	87	84	81	79	76	
取付高さ	器具間隔最大限		2.5	97	93	89	86	96	92	88	85	92	89	86	84	89	87	84	82	79
	横方向 (A)	縦方向 (B)	3.0	99	95	92	89	97	94	91	88	94	91	89	86	91	89	87	85	81
H m	0.87 H m	0.87 H m	4.0	101	98	95	93	99	97	94	92	96	94	92	90	93	91	89	88	85
			5.0	102	100	98	95	101	98	96	94	97	95	94	92	94	93	91	90	86
			7.0	104	102	100	99	102	100	99	97	99	97	96	95	96	95	94	93	89
			10.0	105	104	102	101	103	102	101	100	100	99	98	97	97	96	95	95	91

