

屋内照明器具特性

| | | |
|---------|---------------------|-------------|
| 品番 (品名) | NYM20141K+NYK00101 | |
| 光源 | LED5000_85_14000 ×1 | 14000.0 1 m |
| 管理番号 | K0168490(0)DY1 | |
| BZ分類 | BZ2 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 0% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 下方光束 | 100% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 中 否 | 0.77 | 0.6 | 71 | 62 | 57 | 53 | 70 | 62 | 56 | 53 | 68 | 61 | 56 | 52 | 67 | 60 | 56 | 52 | 51 | |
| | | 0.72 | 0.8 | 80 | 72 | 66 | 62 | 79 | 71 | 66 | 62 | 77 | 70 | 65 | 62 | 75 | 69 | 65 | 62 | 60 | |
| | | 0.68 | 1.0 | 85 | 78 | 73 | 69 | 84 | 77 | 72 | 69 | 82 | 76 | 72 | 68 | 80 | 75 | 71 | 68 | 66 | |
| | | | 1.25 | 90 | 83 | 78 | 75 | 88 | 83 | 78 | 74 | 86 | 81 | 77 | 74 | 84 | 80 | 76 | 73 | 72 | |
| 下方投影面積 | c m ² | 1.5 | 93 | 87 | 82 | 79 | 91 | 86 | 82 | 79 | 89 | 85 | 81 | 78 | 87 | 83 | 80 | 77 | 75 | | |
| | | 2.0 | 96 | 92 | 88 | 85 | 95 | 91 | 87 | 84 | 93 | 89 | 86 | 84 | 91 | 88 | 85 | 83 | 81 | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 99 | 95 | 92 | 89 | 98 | 94 | 91 | 88 | 95 | 92 | 89 | 87 | 93 | 90 | 88 | 86 | 84 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 100 | 97 | 94 | 91 | 99 | 96 | 93 | 91 | 97 | 94 | 92 | 90 | 95 | 92 | 90 | 89 | 86 | |
| H m | 0.95 H m | 0.95 H m | 4.0 | 102 | 100 | 97 | 95 | 101 | 99 | 96 | 95 | 99 | 97 | 95 | 93 | 97 | 95 | 93 | 92 | 89 | |
| | | | 5.0 | 104 | 101 | 99 | 98 | 102 | 100 | 98 | 97 | 100 | 98 | 97 | 95 | 98 | 96 | 95 | 94 | 91 | |
| | | | 7.0 | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 100 | 101 | 100 | 99 | 98 | 99 | 98 | 97 | 96 | 94 | |
| | | | 10.0 | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 102 | 102 | 101 | 100 | 100 | 99 | 99 | 98 | 95 | |

