

屋内照明器具特性

品番 (品名)	NWCF11100C (JYOUJI)	
光源	LED5000_85_630 x1	630.0 l m
管理番号	K0153286 (2) DB 1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		2%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		98%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	55	43	35	29	54	42	34	29	51	41	34	29	49	40	33	29	26	
	中	0.81	0.8	65	53	45	39	63	52	45	39	60	51	44	39	58	49	43	38	36	
	否	0.77	1.0	72	61	53	46	70	60	52	46	67	58	51	46	64	56	50	45	43	
			1.25	78	67	60	54	76	66	59	53	72	64	58	53	69	62	57	52	49	
下方投影面積	c m ²		1.5	82	72	65	59	80	71	64	59	76	69	63	58	73	67	62	57	54	
	等価発光面積		c m ²	2.0	87	79	73	68	85	78	72	67	82	76	70	66	79	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	83	77	73	86	80	75	71	82	78	74	70	67	
	横方向 (A)	縦方向 (B)	3.0	94	87	82	78	92	86	81	77	88	83	79	75	85	81	77	74	71	
H m	1.29 H m	1.29 H m	4.0	97	92	87	84	95	90	86	83	92	88	84	81	88	85	82	79	76	
			5.0	99	95	91	87	97	93	90	87	94	90	87	85	90	88	85	83	80	
			7.0	101	98	95	92	99	97	94	91	96	94	91	89	93	91	89	87	84	
			10.0	103	101	98	96	101	99	97	95	98	96	95	93	95	94	92	91	87	

