

屋内照明器具特性	
品番 (品名)	NWCF13501C(JYOUJI)
光源	LED2700_85_595 x1 595.0 l m
管理番号	K0168122(0)DR1
BZ分類	BZ9

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	50%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	4.4	3.2	2.4	1.8	4.0	2.9	2.2	1.7	3.3	2.4	1.8	1.4	2.6	1.9	1.4	1.1	6
	中	0.81	0.8	5.2	4.0	3.1	2.5	4.8	3.7	2.9	2.3	3.9	3.0	2.4	1.9	3.1	2.4	1.9	1.6	9
	否	0.77	1.0	5.8	4.6	3.7	3.1	5.3	4.2	3.5	2.9	4.3	3.5	2.9	2.4	3.5	2.8	2.3	1.9	11
			1.25	6.4	5.2	4.4	3.7	5.8	4.8	4.0	3.4	4.8	4.0	3.4	2.9	3.8	3.2	2.7	2.3	14
下方投影面積		cm ²	1.5	6.8	5.7	4.9	4.2	6.2	5.2	4.5	3.9	5.1	4.3	3.8	3.3	4.1	3.5	3.1	2.7	17
等価発光面積		cm ²	2.0	7.3	6.4	5.6	5.0	6.7	5.9	5.2	4.6	5.5	4.9	4.4	3.9	4.5	4.0	3.6	3.2	2.0
取付高さ	器具間隔最大限		2.5	7.7	6.9	6.2	5.6	7.1	6.3	5.7	5.2	5.9	5.3	4.8	4.4	4.7	4.3	3.9	3.6	2.3
	横方向 (A)	縦方向 (B)	3.0	7.9	7.2	6.6	6.0	7.3	6.6	6.1	5.6	6.1	5.6	5.1	4.7	5.0	4.6	4.2	3.9	2.6
Hm	1.35Hm	1.53Hm	4.0	8.3	7.7	7.1	6.6	7.7	7.1	6.6	6.2	6.4	6.0	5.6	5.2	5.2	4.9	4.6	4.3	2.9
			5.0	8.5	8.0	7.5	7.1	7.9	7.4	7.0	6.6	6.6	6.3	5.9	5.6	5.4	5.2	4.9	4.6	3.2
			7.0	8.8	8.4	8.0	7.6	8.2	7.8	7.4	7.1	6.9	6.6	6.3	6.1	5.7	5.5	5.3	5.0	3.5
			10.0	9.0	8.7	8.4	8.1	8.4	8.1	7.8	7.6	7.1	6.9	6.7	6.5	5.9	5.7	5.6	5.4	3.8

