

屋内照明器具特性	
品番(品名)	NWCF59191C(JYOUJI)
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 l m
管理番号	K0174187(1)DR1
BZ分類	BZ10

器具効率	33%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	16%	床	10%				10%				10%				10%				0%	
下方光束	17%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	14	10	7	5	13	9	6	4	10	7	5	4	8	6	4	3	1	
	中 0.6	0.8	16	12	9	7	15	11	8	7	12	9	7	5	10	7	5	4	2	
	否 0.56	1.0	18	14	11	9	17	13	10	8	14	11	8	7	11	8	7	5	3	
		1.25	20	16	13	11	18	15	12	10	15	12	10	8	12	10	8	7	4	
下方投影面積	cm ²	1.5	22	18	15	13	20	16	14	12	16	14	11	10	13	11	9	8	4	
等価発光面積		2.0	24	20	18	15	21	19	16	14	18	15	13	12	14	12	11	10	6	
取付高さ	器具間隔最大限		2.5	25	22	19	17	23	20	18	16	19	17	15	13	15	14	12	11	7
H m	横方向(A)	縦方向(B)	3.0	26	23	21	19	24	21	19	17	20	18	16	15	16	14	13	12	8
	0.00H m	0.00H m	4.0	27	25	23	21	25	23	21	20	21	19	18	17	17	16	15	14	9
			5.0	28	26	24	23	26	24	22	21	22	20	19	18	18	17	16	15	10
			7.0	29	27	26	25	27	25	24	23	22	21	20	19	19	18	17	16	11
			10.0	30	28	27	26	27	26	25	24	23	22	22	21	19	19	18	17	12

