

屋内照明器具特性	
品番 (品名)	NWCF59192 (JYOUJI)
光源	LDA7D-G-E17/Z60E/S/W/2 ×1 760.0 lm
管理番号	K0169812 (1) DR1
BZ分類	BZ10

器具効率	33%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	16%	床	10%				10%				10%				10%				0%	
下方光束	17%		10%				10%				10%				10%				0%	
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	1.4	1.0	0.7	0.5	1.2	0.9	0.6	0.4	1.0	0.7	0.5	0.4	0.8	0.6	0.4	0.3	1
	中	0.6	0.8	1.6	1.2	0.9	0.7	1.5	1.1	0.8	0.6	1.2	0.9	0.7	0.5	0.9	0.7	0.5	0.4	2
	否	0.56	1.0	1.8	1.4	1.1	0.9	1.7	1.3	1.0	0.8	1.4	1.1	0.8	0.7	1.1	0.8	0.7	0.5	3
			1.25	2.0	1.6	1.3	1.1	1.8	1.5	1.2	1.0	1.5	1.2	1.0	0.8	1.2	1.0	0.8	0.7	4
下方投影面積		cm ²	1.5	2.2	1.8	1.5	1.3	2.0	1.6	1.4	1.2	1.6	1.3	1.1	1.0	1.3	1.1	0.9	0.8	4
等価発光面積		cm ²	2.0	2.3	2.0	1.8	1.5	2.1	1.9	1.6	1.4	1.8	1.5	1.3	1.2	1.4	1.2	1.1	1.0	6
取付高さ	器具間隔最大限		2.5	2.5	2.2	1.9	1.7	2.3	2.0	1.8	1.6	1.9	1.7	1.5	1.3	1.5	1.4	1.2	1.1	7
	横方向 (A)	縦方向 (B)	3.0	2.6	2.3	2.1	1.9	2.4	2.1	1.9	1.7	2.0	1.8	1.6	1.5	1.6	1.4	1.3	1.2	8
Hm	0.00Hm	0.00Hm	4.0	2.7	2.5	2.3	2.1	2.5	2.3	2.1	1.9	2.1	1.9	1.8	1.6	1.7	1.6	1.5	1.4	9
			5.0	2.8	2.6	2.4	2.2	2.6	2.4	2.2	2.1	2.1	2.0	1.9	1.8	1.8	1.7	1.6	1.5	10
			7.0	2.9	2.7	2.6	2.4	2.6	2.5	2.4	2.3	2.2	2.1	2.0	1.9	1.8	1.8	1.7	1.6	1.1
			10.0	2.9	2.8	2.7	2.6	2.7	2.6	2.5	2.4	2.3	2.2	2.2	2.1	1.9	1.9	1.8	1.7	1.2

