

屋内照明器具特性	
品番 (品名)	NWCF59192J (J YOUJI)
光源	LDA8D- D- G- E17 / S / Z6 ×1 760.0 l m
管理番号	K0174187 (1) DR 1
BZ分類	BZ10

器具効率	33 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	16 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	17 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	1.4	1.0	0.7	0.5	1.3	0.9	0.6	0.4	1.0	0.7	0.5	0.4	0.8	0.6	0.4	0.3	1
	中	0.6	0.8	1.6	1.2	0.9	0.7	1.5	1.1	0.8	0.7	1.2	0.9	0.7	0.5	1.0	0.7	0.5	0.4	2
	否	0.56	1.0	1.8	1.4	1.1	0.9	1.7	1.3	1.0	0.8	1.4	1.1	0.8	0.7	1.1	0.8	0.7	0.5	3
			1.25	2.0	1.6	1.3	1.1	1.8	1.5	1.2	1.0	1.5	1.2	1.0	0.8	1.2	1.0	0.8	0.7	4
下方投影面積		cm ²	1.5	2.2	1.8	1.5	1.3	2.0	1.6	1.4	1.2	1.6	1.4	1.1	1.0	1.3	1.1	0.9	0.8	4
等価発光面積		cm ²	2.0	2.4	2.0	1.8	1.5	2.1	1.9	1.6	1.4	1.8	1.5	1.3	1.2	1.4	1.2	1.1	1.0	6
取付高さ	器具間隔最大限		2.5	2.5	2.2	1.9	1.7	2.3	2.0	1.8	1.6	1.9	1.7	1.5	1.3	1.5	1.4	1.2	1.1	7
	横方向 (A)	縦方向 (B)	3.0	2.6	2.3	2.1	1.9	2.4	2.1	1.9	1.7	2.0	1.8	1.6	1.5	1.6	1.4	1.3	1.2	8
H _m	0.00H _m	0.00H _m	4.0	2.7	2.5	2.3	2.1	2.5	2.3	2.1	2.0	2.1	1.9	1.8	1.7	1.7	1.6	1.5	1.4	9
			5.0	2.8	2.6	2.4	2.3	2.6	2.4	2.2	2.1	2.2	2.0	1.9	1.8	1.8	1.7	1.6	1.5	10
			7.0	2.9	2.7	2.6	2.5	2.7	2.5	2.4	2.3	2.2	2.1	2.0	1.9	1.9	1.8	1.7	1.6	1.1
			10.0	3.0	2.8	2.7	2.6	2.7	2.6	2.5	2.4	2.3	2.2	2.2	2.1	1.9	1.9	1.8	1.7	1.2

