

屋内照明器具特性	
品番 (品名)	NWCF59310 (JYOUJI)
光源	LED5000_70_490 x1 490.0 l m
管理番号	K0185161 (2) DR 1
BZ分類	BZ9

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	4.4	3.1	2.3	1.8	4.0	2.9	2.1	1.6	3.3	2.4	1.8	1.3	2.6	1.9	1.4	1.0	5
	中	0.6	0.8	5.2	4.0	3.1	2.5	4.8	3.6	2.9	2.3	3.9	3.0	2.4	1.9	3.1	2.4	1.9	1.5	9
	否	0.56	1.0	5.8	4.6	3.7	3.1	5.3	4.2	3.4	2.9	4.3	3.5	2.9	2.4	3.5	2.8	2.3	1.9	11
			1.25	6.4	5.2	4.4	3.7	5.8	4.8	4.0	3.4	4.8	4.0	3.4	2.9	3.8	3.2	2.7	2.3	14
下方投影面積		cm <sup>2</sup>	1.5	6.8	5.7	4.9	4.2	6.2	5.3	4.5	3.9	5.1	4.4	3.8	3.3	4.1	3.5	3.1	2.7	17
等価発光面積		cm <sup>2</sup>	2.0	7.3	6.4	5.7	5.0	6.7	5.9	5.2	4.7	5.6	4.9	4.4	3.9	4.5	4.0	3.6	3.2	2.1
取付高さ	器具間隔最大限		2.5	7.7	6.9	6.2	5.6	7.1	6.4	5.7	5.2	5.9	5.3	4.8	4.4	4.8	4.3	4.0	3.6	2.4
	横方向 (A)	縦方向 (B)	3.0	8.0	7.2	6.6	6.1	7.3	6.7	6.1	5.6	6.1	5.6	5.2	4.8	5.0	4.6	4.2	3.9	2.6
H <sub>m</sub>	0.00H <sub>m</sub>	1.85H <sub>m</sub>	4.0	8.3	7.7	7.2	6.7	7.7	7.1	6.7	6.2	6.4	6.0	5.6	5.3	5.3	5.0	4.7	4.4	3.0
			5.0	8.6	8.0	7.6	7.1	7.9	7.4	7.0	6.6	6.7	6.3	6.0	5.6	5.5	5.2	4.9	4.7	3.2
			7.0	8.8	8.4	8.0	7.7	8.2	7.8	7.5	7.2	6.9	6.6	6.4	6.1	5.7	5.5	5.3	5.1	3.6
			10.0	9.1	8.8	8.5	8.2	8.4	8.1	7.9	7.6	7.2	6.9	6.7	6.5	6.0	5.8	5.6	5.4	3.9

