

屋内照明器具特性

品番 (品名)	XAD11013				
光源	LLD20003CQ1	×1	531.0	lm	
管理番号	K0175548(0)DR1				
BZ分類	BZ4/0.7/BZ3				

器具効率	64%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		64%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	3.9	3.2	2.7	2.4	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.5	3.0	2.6	2.4	2.3	
	中	0.63	0.8	4.6	3.9	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0	
	否	0.56	1.0	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.7	4.7	4.3	3.9	3.6	4.6	4.2	3.9	3.6	3.5	
			1.25	5.4	4.9	4.5	4.2	5.3	4.8	4.4	4.1	5.1	4.7	4.4	4.1	5.0	4.6	4.3	4.1	3.9	
下方投影面積			c m ²																		
			等価発光面積																		
取付高さ	器具間隔最大限		c m ²																		
	H m	1.25 H m	1.25 H m	H m																	
			2.5	6.1	5.8	5.5	5.3	6.0	5.8	5.5	5.3	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.2	5.0	
			3.0	6.3	6.0	5.8	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.2	
			4.0	6.4	6.2	6.0	5.8	6.3	6.1	6.0	5.8	6.2	6.0	5.9	5.7	6.0	5.9	5.8	5.6	5.5	
			5.0	6.5	6.4	6.2	6.0	6.4	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6	
			7.0	6.6	6.5	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	5.8	
			10.0	6.7	6.6	6.5	6.5	6.6	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.3	6.3	6.2	6.2	6.0	

