

屋内照明器具特性

品番 (品名)	NYT 1 1 0 1	
光源	LLD3020LCE1 ×1	795.0 lm
管理番号	K0198495 (0) DB 1	
B Z 分類	B Z 1	

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	86 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	67	61	56	54	66	60	56	54	65	60	56	53	64	59	56	53	52	
	中	0.6	0.8	73	68	64	61	73	67	63	61	71	66	63	60	70	66	63	60	59	
	否	0.56	1.0	77	72	68	66	76	72	68	66	75	71	68	65	73	70	67	65	64	
			1.25	81	76	73	70	80	75	72	70	78	74	72	69	76	73	71	69	68	
下方投影面積	c m ²		1.5	83	79	75	73	82	78	75	73	80	77	74	72	78	76	73	72	70	
	等価発光面積		c m ²	2.0	85	82	79	77	84	81	79	77	83	80	78	76	81	79	77	75	74
取付高さ	器具間隔最大限		2.5	87	84	82	80	86	84	81	80	84	82	80	79	82	81	79	78	76	
	横方向 (A)	縦方向 (B)	3.0	88	86	84	82	87	85	83	81	85	83	82	80	83	82	81	79	78	
H m	0.79 H m	0.79 H m	4.0	89	88	86	84	88	87	85	84	87	85	84	83	85	84	83	82	80	
			5.0	90	89	87	86	89	88	87	85	87	86	85	84	86	85	84	83	81	
			7.0	91	90	89	88	90	89	88	87	88	87	87	86	86	86	85	85	82	
			10.0	92	91	90	90	91	90	89	89	89	88	88	87	87	87	86	86	83	

