

屋内照明器具特性

品番 (品名)	NYT 1 1 0 1														
光源	LLD4000LCB1 ×1 845.0 l m														
管理番号	K0198338 (0) DB 1														
B Z 分類	B Z 3														

器具効率	48 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X 0 . 0 1)															Z C M			
下方光束	48 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	30	24	21	19	29	24	21	19	28	24	21	19	27	23	21	19	18		
		0.8	34	30	26	24	34	29	26	24	33	29	26	24	32	28	26	24	23		
		1.0	37	33	30	28	37	33	30	28	36	32	29	27	34	31	29	27	26		
		1.25	40	36	33	31	39	36	33	31	38	35	33	31	37	34	32	31	30		
下方投影面積	c m ²	1.5	42	38	36	34	41	38	35	33	40	37	35	33	39	36	34	33	32		
		2.0	44	41	39	37	44	41	39	37	42	40	38	37	41	39	38	36	35		
取付高さ	器具間隔最大限		2.5	46	43	41	40	45	43	41	39	44	42	40	39	43	41	40	38	37	
	横方向 (A)	縦方向 (B)	3.0	47	45	43	41	46	44	42	41	45	43	42	40	44	42	41	40	39	
H m	1.19 H m	1.19 H m	4.0	48	46	45	43	47	46	44	43	46	45	44	43	45	44	43	42	41	
			5.0	49	47	46	45	48	47	46	45	47	46	45	44	46	45	44	43	42	
			7.0	49	48	48	47	49	48	47	46	48	47	46	45	46	46	45	45	43	
			10.0	50	49	49	48	49	49	48	48	48	48	47	47	47	47	46	46	45	

