

屋外照明器具特性

| | | | | | | | | | | | | | | | | | | | | |
|--------------------------|-----------------------|--------|----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|
| 品番(品名) | NYT2104 | | | | | | | | | | | | | | | | | | | |
| 光源 | LDA13L-G/Z100E/S/W x1 | 1520.0 | lm | | | | | | | | | | | | | | | | | |
| 管理番号 | K0157595(1)DB1 | | | | | | | | | | | | | | | | | | | |
| JISC8131-1999 による配光形式 | | | | | | | | | | | | | | | | | | | | |
| 器具効率 | 23.1% | 直下光度 | 0.0 cd/1000lm | | | | | | | | | | | | | | | | | |
| 上方光束 | 9.7% | 最大光度 | 37.4 cd/1000lm | | | | | | | | | | | | | | | | | |
| 下方光束 | 13.3% | | | | | | | | | | | | | | | | | | | |
| 鉛直角 | 0° | 5° | 10° | 15° | 20° | 25° | 30° | 35° | 40° | 45° | 50° | 55° | 60° | 65° | 70° | 75° | 80° | 85° | 90° | |
| =0°鉛直面 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 4 | 8 | 12 | 16 | 21 | 25 | 29 | 33 | 35 | 37 | 37 | 36 | |
| 90° | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 4 | 7 | 11 | 16 | 20 | 25 | 29 | 33 | 35 | 37 | 37 | 36 | |
| 180° | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 4 | 8 | 12 | 16 | 21 | 25 | 29 | 33 | 35 | 37 | 37 | 36 | |
| 270° | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 4 | 7 | 11 | 16 | 20 | 25 | 29 | 33 | 35 | 37 | 37 | 36 | |
| I _{max} を含む鉛直面 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 4 | 7 | 11 | 16 | 20 | 25 | 29 | 32 | 35 | 37 | 37 | 36 | |

