

# 屋内照明器具特性

品番 (品名)	XAD3 1 0 0 5 K				
光源	LLD4 0 0 0 5 CQ1 ×1		845.0 l m		
管理番号	K0175549 ( 0 ) DR 1				
B Z 分類	BZ4 / 0.7 / BZ3				

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	83 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29
	中	0.63	0.8	59	51	45	41	58	50	45	41	56	49	44	40	54	48	44	40	39
	否	0.56	1.0	65	57	52	48	64	57	51	47	62	55	51	47	60	54	50	47	45
			1.25	70	63	58	54	69	62	57	54	66	61	57	53	64	60	56	53	51
下方投影面積	c m <sup>2</sup>		1.5	73	67	62	58	72	66	62	58	69	65	61	58	67	63	60	57	55
等価発光面積	c m <sup>2</sup>		2.0	77	72	68	65	76	71	67	64	74	70	66	64	72	68	65	63	61
取付高さ	器具間隔最大限		2.5	80	75	72	69	78	75	71	68	76	73	70	68	74	71	69	67	65
	横方向 (A)	縦方向 (B)	3.0	81	78	75	72	80	77	74	71	78	75	73	70	76	74	71	70	68
H m	1.25 H m	1.25 H m	4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71
			5.0	85	82	80	78	84	81	79	78	81	80	78	76	79	78	77	75	73
			7.0	86	84	83	81	85	83	82	81	83	82	80	79	81	80	79	78	76
			10.0	87	86	85	84	86	85	84	83	84	83	82	81	82	81	81	80	78

