

屋内照明器具特性

品番 (品名)	XAD3 1 0 1 1														
光源	LLD40001CQ1 ×1 845.0 1 m														
管理番号	K0175547 (0) DR 1														
BZ分類	BZ4 / 0.7 / BZ3														

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	64 %																				
保守率	良 中 否	0.67	0.6	3.9	3.2	2.7	2.4	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.5	3.0	2.6	2.4	2.3	
		0.63	0.8	4.6	3.9	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0	
		0.56	1.0	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.6	4.7	4.3	3.9	3.6	4.6	4.2	3.9	3.6	3.5	
			1.25	5.4	4.8	4.5	4.1	5.3	4.8	4.4	4.1	5.1	4.7	4.4	4.1	4.9	4.6	4.3	4.1	3.9	
下方投影面積	c m ²	1.5	5.6	5.1	4.8	4.5	5.5	5.1	4.7	4.5	5.3	5.0	4.7	4.4	5.2	4.9	4.6	4.4	4.3		
		2.0	5.9	5.6	5.2	5.0	5.8	5.5	5.2	5.0	5.7	5.4	5.1	4.9	5.5	5.3	5.0	4.9	4.7		
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.3	6.0	5.7	5.5	5.3	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.1	5.0	
	横方向 (A)	縦方向 (B)	3.0	6.3	6.0	5.7	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.8	5.7	5.5	5.4	5.2	
H m	1.25 H m	1.25 H m	4.0	6.4	6.2	6.0	5.8	6.3	6.1	6.0	5.8	6.2	6.0	5.8	5.7	6.0	5.9	5.7	5.6	5.5	
			5.0	6.5	6.3	6.2	6.0	6.4	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6	
			7.0	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.2	6.1	6.0	5.8	
			10.0	6.7	6.6	6.5	6.4	6.6	6.5	6.5	6.4	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.0	

