

# 屋内照明器具特性

品番 (品名)	XAD3 1 0 1 4														
光源	LLD40004CQ1 ×1                      845.0 1 m														
管理番号	K0175547 ( 0 ) DR 1														
BZ分類	BZ4 / 0.7 / BZ3														

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %																			
下方光束	64 %																			
		室指数	照明率 ( X0.01 )                      ZCM																	
保守率	良	0.67	0.6	3.9	3.2	2.7	2.4	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.5	3.0	2.6	2.4	2.3
	中	0.63	0.8	4.6	3.9	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0
	否	0.56	1.0	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.6	4.7	4.3	3.9	3.6	4.6	4.2	3.9	3.6	3.5
			1.25	5.4	4.8	4.5	4.1	5.3	4.8	4.4	4.1	5.1	4.7	4.4	4.1	4.9	4.6	4.3	4.1	3.9
下方投影面積			c m <sup>2</sup>																	
等価発光面積			c m <sup>2</sup>																	
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.3	6.0	5.7	5.5	5.3	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.1	5.0
	横方向 (A)	縦方向 (B)	3.0	6.3	6.0	5.7	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.8	5.7	5.5	5.4	5.2
H <sub>m</sub>	1.25 H <sub>m</sub>	1.25 H <sub>m</sub>	4.0	6.4	6.2	6.0	5.8	6.3	6.1	6.0	5.8	6.2	6.0	5.8	5.7	6.0	5.9	5.7	5.6	5.5
			5.0	6.5	6.3	6.2	6.0	6.4	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6
			7.0	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.2	6.1	6.0	5.8
			10.0	6.7	6.6	6.5	6.4	6.6	6.5	6.5	6.4	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.0

