

屋内照明器具特性

品番 (品名)	NYM20115Z+NYK00109	
光源	LED5000_85_36100 ×1	36100.0 1 m
管理番号	K0174956(2)D 1	
BZ分類	BZ1/1.4/BZ2	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 1%		下方光束 99%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.77	0.6	72	64	58	54	71	63	58	54	69	62	58	54	68	61	57	54	52	
	中	0.72	0.8	80	73	67	63	79	72	67	63	77	71	66	63	75	70	66	62	61	
	否	0.68	1.0	86	78	73	69	84	78	73	69	82	76	72	69	80	75	71	68	67	
	下方投影面積	c m ²		1.25	90	84	79	75	89	83	78	75	86	81	77	74	84	80	76	74	72
等価発光面積	c m ²		1.5	93	87	83	79	91	86	82	79	89	84	81	78	87	83	80	77	75	
	c m ²		2.0	96	92	88	85	95	91	87	84	93	89	86	83	90	87	85	82	80	
取付高さ	器具間隔最大限		2.5	99	95	91	89	97	94	91	88	95	92	89	87	92	90	88	86	83	
	H m	0.83 H m	0.83 H m	3.0	100	97	94	91	99	96	93	91	96	94	91	89	94	92	90	88	86
H m	H m		4.0	102	100	97	95	101	98	96	94	98	96	94	93	96	94	93	91	89	
	H m		5.0	103	101	99	97	102	100	98	96	99	98	96	95	97	96	94	93	90	
	H m		7.0	105	103	102	100	103	102	100	99	101	100	98	97	98	97	96	95	93	
	H m		10.0	106	105	103	102	104	103	102	101	102	101	100	99	99	99	98	97	94	

