

屋内照明器具特性	
品番 (品名)	NYM20121Z+NYK00106
光源	LED5000_85_14700 ×1 14700.0 lm
管理番号	K0174958(0)D 1
BZ分類	BZ3/0.7/BZ2/1.8/BZ3/8.5/BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	66	56	49	45	65	55	49	45	63	54	49	45	61	53	48	44	43
	中	0.81	0.8	76	66	60	56	74	66	60	55	72	64	59	55	70	63	59	55	53
	否	0.77	1.0	82	73	67	63	80	73	67	63	78	71	66	62	76	70	65	62	60
			1.25	87	79	74	70	85	79	73	69	83	77	72	69	80	75	72	68	66
下方投影面積	cm ²		1.5	90	84	79	74	89	83	78	74	86	81	77	73	84	79	76	73	71
	等価発光面積		2.0	95	89	85	81	93	88	84	81	91	86	83	80	88	85	82	79	77
取付高さ	器具間隔最大限		2.5	97	93	89	86	96	92	88	85	93	90	87	84	91	88	85	83	81
	横方向 (A)	縦方向 (B)	3.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	86	83
Hm	1.07Hm	1.07Hm	4.0	101	98	96	93	100	97	95	92	97	95	93	91	95	93	91	90	87
			5.0	103	100	98	96	101	99	97	95	99	97	95	94	96	95	93	92	89
			7.0	104	102	101	99	103	101	100	98	100	99	98	96	98	97	96	95	92
			10.0	105	104	103	102	104	103	102	101	102	101	100	99	99	98	98	97	94

