

屋内照明器具特性	
品番 (品名)	NYM20143K+NYK00101
光源	LED5000_85_21900 ×1 21900.0 1m
管理番号	K0168490(0)DY1
BZ分類	BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	100%	室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.77	0.6	71	62	57	53	70	62	56	53	68	61	56	52	67	60	56	52	51			
		0.72	0.8	80	72	66	62	79	71	66	62	77	70	65	62	75	69	65	62	60			
		0.68	1.0	85	78	73	69	84	77	72	69	82	76	72	68	80	75	71	68	66			
			1.25	90	83	78	75	88	83	78	74	86	81	77	74	84	80	76	73	72			
下方投影面積	c m <sup>2</sup>	1.5	93	87	82	79	91	86	82	79	89	85	81	78	87	83	80	77	75				
		2.0	96	92	88	85	95	91	87	84	93	89	86	84	91	88	85	83	81				
取付高さ	器具間隔最大限		2.5	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	86				
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89				
H m	0.95 H m	0.95 H m	4.0	102	100	97	95	101	99	96	95	99	97	95	93	97	95	93	92				
			5.0	104	101	99	98	102	100	98	97	100	98	97	95	98	96	95	94	91			
			7.0	105	103	102	100	104	102	101	100	101	100	99	98	99	98	97	96				
			10.0	106	105	104	103	105	104	103	102	102	102	101	100	100	99	99	98				

