

|          |                                |
|----------|--------------------------------|
| 屋内照明器具特性 |                                |
| 品番(品名)   | NYM20171K                      |
| 光源       | LED5000_85_16000 ×1 16000.0 1m |
| 管理番号     | K0172770(4)DR1                 |
| BZ分類     | BZ1/1.1/BZ2                    |

|        |                  |          |             |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |    |
|--------|------------------|----------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|----|
| 器具効率   | 100%             | 天井       | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |    |    |    | 0%  |    |
|        |                  | 壁        | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 1%               | 床        | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0%  |    |
| 下方光束   | 99%              | 室指数      | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |    |
| 保守率    | 良                | 0.83     | 0.6         | 73  | 64  | 59  | 55  | 72  | 64  | 59  | 55  | 70  | 63  | 58  | 55  | 68 | 62 | 58 | 55  | 53 |
|        | 中                | 0.81     | 0.8         | 81  | 73  | 67  | 63  | 79  | 72  | 67  | 63  | 77  | 71  | 66  | 63  | 75 | 70 | 66 | 63  | 61 |
|        | 否                | 0.77     | 1.0         | 85  | 78  | 73  | 69  | 84  | 78  | 73  | 69  | 82  | 76  | 72  | 69  | 80 | 75 | 71 | 68  | 66 |
|        |                  |          | 1.25        | 90  | 83  | 78  | 75  | 88  | 82  | 78  | 74  | 86  | 81  | 77  | 74  | 84 | 79 | 76 | 73  | 71 |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 92          | 87  | 82  | 79  | 91  | 86  | 82  | 78  | 89  | 84  | 80  | 77  | 86  | 83 | 79 | 77 | 75  |    |
|        |                  | 2.0      | 96          | 91  | 87  | 84  | 95  | 90  | 87  | 84  | 92  | 89  | 85  | 83  | 90  | 87 | 84 | 82 | 80  |    |
| 取付高さ   | 器具間隔最大限          |          | 2.5         | 99  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 91  | 89  | 86  | 92 | 89 | 87 | 85  | 83 |
|        | 横方向(A)           | 縦方向(B)   | 3.0         | 100 | 97  | 93  | 91  | 99  | 95  | 93  | 90  | 96  | 93  | 91  | 89  | 94 | 91 | 89 | 88  | 85 |
| H m    | 0.84 H m         | 0.84 H m | 4.0         | 102 | 99  | 97  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 92  | 96 | 94 | 92 | 91  | 88 |
|        |                  |          | 5.0         | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 99  | 98  | 96  | 94  | 97 | 95 | 94 | 93  | 90 |
|        |                  |          | 7.0         | 105 | 103 | 101 | 100 | 103 | 102 | 100 | 99  | 101 | 99  | 98  | 97  | 98 | 97 | 96 | 95  | 92 |
|        |                  |          | 10.0        | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 99 | 99 | 98 | 97  | 94 |

