

屋内照明器具特性

| | | |
|---------|-----------------------------|------------|
| 品番 (品名) | NYM20185K+NYK00107 | |
| 光源 | LED5000_85_38800 ×1 | 38800.0 lm |
| 管理番号 | K0174958(0)D 1 | |
| BZ分類 | BZ3/0.7/BZ2/1.8/BZ3/8.5/BZ2 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 1% | | 下方光束 99% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.83 | 0.6 | 66 | 56 | 49 | 45 | 65 | 55 | 49 | 45 | 63 | 54 | 49 | 45 | 61 | 53 | 48 | 44 | 43 |
| | 中 | 0.81 | 0.8 | 76 | 66 | 60 | 56 | 74 | 66 | 60 | 55 | 72 | 64 | 59 | 55 | 70 | 63 | 59 | 55 | 53 |
| | 否 | 0.77 | 1.0 | 82 | 73 | 67 | 63 | 80 | 73 | 67 | 63 | 78 | 71 | 66 | 62 | 76 | 70 | 65 | 62 | 60 |
| | | | 1.25 | 87 | 79 | 74 | 70 | 85 | 79 | 73 | 69 | 83 | 77 | 72 | 69 | 80 | 75 | 72 | 68 | 66 |
| 下方投影面積 | c m ² | | 1.5 | 90 | 84 | 79 | 74 | 89 | 83 | 78 | 74 | 86 | 81 | 77 | 73 | 84 | 79 | 76 | 73 | 71 |
| | 等価発光面積 | | c m ² | 2.0 | 95 | 89 | 85 | 81 | 93 | 88 | 84 | 81 | 91 | 86 | 83 | 80 | 88 | 85 | 82 | 79 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 97 | 93 | 89 | 86 | 96 | 92 | 88 | 85 | 93 | 90 | 87 | 84 | 91 | 88 | 85 | 83 | 81 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 99 | 95 | 92 | 89 | 98 | 94 | 91 | 88 | 95 | 92 | 89 | 87 | 93 | 90 | 88 | 86 | 83 |
| H m | 1.07H m | 1.07H m | 4.0 | 101 | 98 | 96 | 93 | 100 | 97 | 95 | 92 | 97 | 95 | 93 | 91 | 95 | 93 | 91 | 90 | 87 |
| | | | 5.0 | 103 | 100 | 98 | 96 | 101 | 99 | 97 | 95 | 99 | 97 | 95 | 94 | 96 | 95 | 93 | 92 | 89 |
| | | | 7.0 | 104 | 102 | 101 | 99 | 103 | 101 | 100 | 98 | 100 | 99 | 98 | 96 | 98 | 97 | 96 | 95 | 92 |
| | | | 10.0 | 105 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99 | 99 | 98 | 98 | 97 | 94 |

