

# 屋内照明器具特性

品番 (品名)	NYM20181K+NYK00101	
光源	LED5000_85_14200 ×1	14200.0 1 m
管理番号	K0174957(0)D 1	
BZ分類	BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束		1 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
	下方光束		99 %	壁	10 %				10 %				10 %				10 %				0 %		
室指数		床	照明率 ( X0.01 )																				ZCM
保守率	良	0.77	0.6	65	55	49	44	64	55	48	44	62	54	48	44	60	53	47	44	42			
	中	0.72	0.8	75	66	59	55	74	65	59	54	71	64	58	54	69	63	58	54	52			
	否	0.68	1.0	81	73	67	62	80	72	66	62	77	70	65	61	75	69	65	61	59			
			1.25	86	79	73	69	85	78	73	68	82	76	72	68	80	75	71	67	65			
下方投影面積	c m <sup>2</sup>		1.5	90	83	78	74	88	82	77	73	86	80	76	72	83	79	75	72	70			
	等価発光面積		c m <sup>2</sup>	2.0	94	89	84	80	93	88	84	80	90	86	82	79	88	84	81	78	76		
取付高さ	器具間隔最大限		2.5	97	92	88	85	96	91	88	84	93	89	86	83	90	87	85	82	80			
	横方向 (A)	縦方向 (B)	3.0	99	95	91	88	97	94	91	88	95	92	89	86	92	90	87	85	83			
H m	1.06 H m	1.06 H m	4.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	89	87			
			5.0	103	100	98	95	101	99	97	95	99	97	95	93	96	95	93	92	89			
			7.0	104	102	100	99	103	101	99	98	100	99	97	96	98	97	96	94	92			
			10.0	105	104	103	101	104	103	102	100	102	101	100	99	99	98	98	97	94			

