

# 屋内照明器具特性

品番 (品名)	NYM20185K+NYK00109	
光源	LED5000_85_35500 ×1	35500.0 lm
管理番号	K0174959(0)D 1	
BZ分類	BZ3/0.7/BZ2/1.8/BZ3	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	99%	床		10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良 中 否	0.77	0.6	66	55	49	44	64	55	49	44	62	54	48	44	60	53	48	44	42	
		0.72	0.8	75	66	60	55	74	65	59	55	71	64	59	54	69	63	58	54	52	
		0.68	1.0	81	73	67	62	80	72	66	62	77	70	65	62	75	69	65	61	59	
			1.25	86	79	73	69	85	78	73	69	82	76	72	68	80	75	71	67	65	
下方投影面積	c m <sup>2</sup>	1.5	90	83	78	74	88	82	77	73	85	80	76	73	83	79	75	72	70		
		2.0	94	89	84	81	93	88	84	80	90	86	82	79	87	84	81	78	76		
取付高さ	器具間隔最大限		2.5	97	92	88	85	95	91	88	85	93	89	86	83	90	87	84	82	80	
	横方向 (A)	縦方向 (B)	3.0	99	95	91	88	97	94	90	88	95	91	89	86	92	89	87	85	82	
H m	1.06H m	1.06H m	4.0	101	98	95	93	100	97	94	92	97	94	92	90	94	92	91	89	86	
			5.0	102	100	98	95	101	99	97	95	98	96	95	93	96	94	93	91	88	
			7.0	104	102	100	99	103	101	99	98	100	98	97	96	97	96	95	94	91	
			10.0	105	104	103	101	104	103	101	100	101	100	99	98	99	98	97	96	93	

