

屋内照明器具特性

品番 (品名)	NYM20200+NYK00116									
光源	LED5000_85_10340 ×1 10340.0 lm									
管理番号	K0185718(0)DB1									
BZ分類	BZ5/0.7/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	97%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.83	0.6	58	46	38	33	56	45	38	33	54	44	37	32	51	42	36	32	30
	中	0.81	0.8	68	57	49	44	66	56	49	43	63	54	48	43	60	53	47	42	40
	否	0.77	1.0	75	64	57	51	73	63	56	51	70	61	55	50	67	60	54	50	47
			1.25	81	71	64	59	79	70	64	59	75	68	62	58	72	66	61	57	55
下方投影面積	cm ²		1.5	85	76	70	65	83	75	69	64	79	73	68	63	76	71	66	62	60
等価発光面積	cm ²		2.0	90	83	78	73	88	82	77	72	85	80	75	71	82	77	73	70	67
取付高さ	器具間隔最大限		2.5	93	88	83	79	92	86	82	78	88	84	80	76	85	81	78	75	72
	横方向 (A)	縦方向 (B)	3.0	96	91	86	83	94	89	85	82	91	87	83	80	88	84	81	79	76
Hm	1.23Hm	1.23Hm	4.0	99	95	91	88	97	93	90	87	94	91	88	85	91	88	86	84	80
			5.0	101	97	94	92	99	96	93	91	96	93	91	89	93	91	89	87	83
			7.0	103	100	98	96	101	99	97	95	98	96	94	92	95	93	92	90	87
			10.0	104	102	101	99	102	101	99	98	99	98	97	96	97	95	94	93	90

