

屋内照明器具特性

品番 (品名)	NYM20201+NYK00111	
光源	LED5000_85_13920 ×1	13920.0 1 m
管理番号	K0185719 (0) DB 1	
BZ分類	BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	7 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	93 %	室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.77	0.6	58	47	39	34	57	46	39	34	54	44	38	33	51	43	37	33	30			
		0.72	0.8	68	57	50	44	66	56	49	44	63	54	48	43	60	52	47	42	40			
			1.0	74	64	57	52	72	63	56	51	69	61	55	50	65	59	53	49	46			
		0.68	1.25	80	71	64	59	78	70	63	58	74	67	62	57	71	65	60	56	53			
下方投影面積	c m ²	1.5	84	76	69	64	82	74	68	64	78	72	66	62	74	69	64	61	57				
		2.0	89	82	77	72	87	81	76	71	83	78	73	70	79	75	71	68	64				
取付高さ	器具間隔最大限		2.5	93	87	82	78	90	85	80	77	86	82	78	75	82	79	76	73	69			
	横方向 (A)	縦方向 (B)	3.0	95	90	85	82	93	88	84	80	89	85	81	78	85	82	79	76	72			
H m	1.20 H m	1.20 H m	4.0	98	94	90	87	96	92	89	86	91	88	86	83	88	85	83	81	77			
			5.0	99	96	93	90	97	94	92	89	93	91	88	86	90	87	86	84	79			
			7.0	101	99	97	95	99	97	95	93	95	94	92	90	92	90	89	87	83			
			10.0	103	101	99	98	101	99	98	96	97	96	94	93	93	92	91	90	85			

