

# 屋内照明器具特性

品番 (品名)	NYM20203 + NYK00118	
光源	LED5000_85_26860 ×1	26860.0 1 m
管理番号	K0185720 (0) DB 1	
BZ分類	BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	8 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	92 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良 中 否	0.77	0.6	58	46	39	34	56	45	38	33	53	44	37	33	51	42	37	32	30			
		0.72	0.8	68	57	49	44	66	56	49	44	62	54	48	43	59	52	46	42	39			
		0.68	1.0	74	64	57	51	72	63	56	51	68	60	55	50	65	58	53	49	46			
			1.25	80	71	64	59	78	69	63	58	74	67	61	57	70	64	59	56	52			
下方投影面積	c m <sup>2</sup>	1.5	84	76	69	64	82	74	68	63	78	71	66	62	74	69	64	60	57				
		2.0	89	82	77	72	87	81	75	71	83	77	73	69	79	75	71	68	64				
取付高さ	器具間隔最大限		2.5	92	86	82	77	90	85	80	76	86	82	78	74	82	78	75	72	68			
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	92	88	84	80	88	84	81	78	84	81	78	76	72			
H m	1.22 H m	1.22 H m	4.0	98	94	90	87	95	92	88	85	91	88	85	83	87	85	83	80	76			
			5.0	99	96	93	90	97	94	91	89	93	91	88	86	89	87	85	83	79			
			7.0	101	99	97	94	99	97	95	93	95	93	92	90	91	90	88	87	82			
			10.0	103	101	99	98	101	99	98	96	97	95	94	93	93	92	91	90	85			

