

屋内照明器具特性

品番 (品名)	NYM20204 + NYK00112	
光源	LED5000_85_36540 ×1	36540.0 lm
管理番号	K0185711 (0) DB 1	
BZ分類	BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	6 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.77	0.6	58	47	40	34	57	46	39	34	54	45	38	34	51	43	37	33	31
		0.72	0.8	68	58	50	45	67	57	50	45	63	55	48	44	60	53	47	43	41
		0.68	1.0	75	65	58	52	73	64	57	52	69	61	56	51	66	59	54	50	47
			1.25	81	72	65	60	79	70	64	59	75	68	62	58	71	65	61	57	54
下方投影面積	c m ²	1.5	84	76	70	65	82	75	69	64	79	72	67	63	75	70	65	62	59	
		2.0	90	83	77	73	88	81	76	72	84	78	74	70	80	76	72	69	65	
取付高さ	器具間隔最大限		2.5	93	87	82	78	91	86	81	77	87	83	79	75	83	80	76	74	70
	横方向 (A)	縦方向 (B)	3.0	95	90	86	82	93	89	85	81	89	85	82	79	86	82	80	77	73
H m	1.23 H m	1.23 H m	4.0	98	94	91	87	96	92	89	86	92	89	86	84	89	86	84	82	78
			5.0	100	97	94	91	98	95	92	90	94	91	89	87	90	88	86	85	81
			7.0	102	99	97	95	100	98	96	94	96	94	92	91	92	91	90	88	84
			10.0	103	102	100	98	101	100	98	97	98	96	95	94	94	93	92	91	87

