

屋内照明器具特性

品番 (品名)	NYM20204+NYK00117														
光源	LED5000_85_39480 ×1 39480.0 1m														
管理番号	K0185710(0)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	98%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.83	0.6	58	46	38	33	56	45	38	33	54	44	37	32	51	43	36	32	30
	中	0.81	0.8	68	57	49	44	66	56	49	43	63	54	48	43	61	53	47	43	40
	否	0.77	1.0	75	64	57	51	73	63	56	51	70	62	55	51	67	60	54	50	48
			1.25	81	71	64	59	79	70	64	59	76	68	63	58	73	66	61	57	55
下方投影面積		cm ²	1.5	85	76	70	65	83	75	69	64	80	73	68	63	77	71	66	63	60
等価発光面積		cm ²	2.0	90	83	78	73	88	82	77	72	85	80	75	71	82	77	74	70	67
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	86	82	78	89	84	80	77	85	82	78	75	72
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	94	90	86	82	91	87	84	80	88	85	82	79	76
Hm	1.27Hm	1.27Hm	4.0	99	95	91	88	97	94	90	87	94	91	88	86	91	88	86	84	81
			5.0	101	97	94	92	99	96	93	91	96	93	91	89	93	91	89	87	84
			7.0	103	100	98	96	101	99	97	95	98	96	94	93	95	94	92	91	87
			10.0	104	102	101	99	103	101	100	98	100	98	97	96	97	96	95	94	90

