

# 屋内照明器具特性

品番 (品名)	NYM20204+NYK00119	
光源	LED5000_85_35700 ×1	35700.0 lm
管理番号	K0185712(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		6%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		94%		壁	10%				10%				10%				10%			
床	10%				10%				10%				10%				0%				
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.77	0.6	58	46	39	34	57	46	39	34	54	44	38	33	51	43	37	33	30	
	中	0.72	0.8	68	57	50	44	66	56	49	44	63	54	48	43	60	52	47	43	40	
	否	0.68	1.0	74	64	57	52	73	63	57	51	69	61	55	50	66	59	54	50	47	
			1.25	80	71	64	59	78	70	64	59	74	67	62	57	71	65	60	56	53	
下方投影面積	c m <sup>2</sup>		1.5	84	76	70	64	82	75	69	64	78	72	67	62	75	69	65	61	58	
	等価発光面積		c m <sup>2</sup>	2.0	89	83	77	72	87	81	76	72	83	78	74	70	80	75	72	68	65
取付高さ	器具間隔最大限		2.5	93	87	82	78	91	85	81	77	87	82	78	75	83	79	76	73	69	
	横方向 (A)	縦方向 (B)	3.0	95	90	86	82	93	88	84	81	89	85	82	79	85	82	79	77	73	
H m	1.25 H m	1.25 H m	4.0	98	94	90	87	96	92	89	86	92	89	86	84	88	86	83	81	77	
			5.0	100	96	93	91	98	95	92	89	94	91	89	87	90	88	86	84	80	
			7.0	102	99	97	95	100	97	95	93	96	94	92	91	92	91	89	88	83	
			10.0	103	101	100	98	101	100	98	97	97	96	95	94	94	93	92	91	86	

