

屋内照明器具特性

品番 (品名)	NYM20213 + NYK00111	
光源	LED5000_85_22500 ×1	22500.0 1 m
管理番号	K0185723 (0) DB 1	
BZ分類	BZ1 / 0.9 / BZ2 / 3.5 / BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	5 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	95 %		室指数	照明率 (X0.01)																			
保守率	良 中 否	0.77	0.6	71	62	57	53	70	62	57	53	68	61	56	52	66	59	55	52	50			
		0.72	0.8	79	71	65	61	77	70	64	61	75	68	64	60	72	67	63	59	57			
		0.68	1.0	83	76	71	67	82	75	70	66	79	73	69	65	76	71	68	65	62			
			1.25	88	81	76	72	86	80	75	71	83	78	74	70	80	76	72	69	67			
下方投影面積	c m ²	1.5	90	84	80	76	89	83	79	75	86	81	77	74	83	79	75	73	70				
		2.0	94	89	85	81	92	88	84	81	89	85	82	79	86	83	80	78	75				
取付高さ	器具間隔最大限		2.5	97	92	88	85	95	91	87	84	91	88	85	83	88	86	83	81	78			
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	96	93	90	87	93	90	88	85	90	87	85	83	80			
H m	0.83 H m	0.83 H m	4.0	100	97	95	92	99	96	93	91	95	93	91	89	92	90	88	87	83			
			5.0	102	99	97	95	100	98	95	93	96	95	93	91	93	92	90	89	85			
			7.0	103	101	99	98	101	100	98	96	98	97	95	94	95	94	92	91	87			
			10.0	104	103	102	100	103	101	100	99	99	98	97	96	96	95	94	93	89			

