

屋内照明器具特性

品番 (品名)	NYM20213 + NYK00116	
光源	LED5000_85_23750 ×1 23750.0 1 m	
管理番号	K0185722 (0) DB 1	
BZ分類	BZ1 / 1.1 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2 / 8.5 / BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	3 %	床	10 %				10 %				10 %				10 %				0 %			
下方光束	97 %	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.83 中 0.81 否 0.77	0.6	73	65	60	56	72	64	59	56	70	63	59	55	68	62	58	55	54			
		0.8	80	73	67	64	79	72	67	63	77	71	66	63	75	69	65	62	61			
		1.0	85	78	73	69	84	77	72	69	81	76	71	68	79	74	70	67	66			
		1.25	89	83	78	74	88	82	77	74	85	80	76	73	83	78	75	72	70			
下方投影面積	c m ²	1.5	92	86	81	78	90	85	81	77	88	83	79	76	85	81	78	75	73			
		2.0	95	91	87	83	94	89	86	83	91	87	84	81	88	85	83	80	78			
取付高さ	器具間隔最大限		2.5	98	94	90	87	96	92	89	86	93	90	87	85	91	88	86	83	81		
	横方向 (A)	縦方向 (B)	3.0	99	96	92	90	98	94	91	89	95	92	90	87	92	90	88	86	83		
H m	0.84 H m	0.84 H m	4.0	101	98	96	93	100	97	95	92	97	95	93	91	94	92	91	89	86		
			5.0	103	100	98	96	101	99	97	95	98	96	94	93	95	94	92	91	89	88	
			7.0	104	102	100	99	102	101	99	98	99	98	97	96	97	96	95	93	90		
			10.0	105	104	102	101	104	102	101	100	101	100	99	98	98	97	96	95	92		

