

| 屋内照明器具特性 | |
|----------|---------------------------------|
| 品番 (品名) | NYM20213+NYK00118 |
| 光源 | LED5000_85_22000 ×1 22000.0 1 m |
| 管理番号 | K0185724(0)DB1 |
| BZ分類 | BZ1/0.7/BZ2/2.8/BZ3 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 5% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 95% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.77 | 0.6 | 71 | 62 | 56 | 52 | 69 | 61 | 56 | 52 | 67 | 60 | 55 | 52 | 65 | 59 | 54 | 51 | 49 |
| | 中 | 0.72 | 0.8 | 78 | 70 | 64 | 60 | 77 | 69 | 64 | 60 | 74 | 68 | 63 | 59 | 72 | 66 | 62 | 59 | 57 |
| | 否 | 0.68 | 1.0 | 83 | 75 | 70 | 66 | 81 | 74 | 69 | 65 | 79 | 73 | 68 | 65 | 76 | 71 | 67 | 64 | 62 |
| | | | 1.25 | 87 | 80 | 75 | 71 | 86 | 79 | 74 | 71 | 82 | 77 | 73 | 70 | 80 | 75 | 72 | 69 | 66 |
| 下方投影面積 | c m ² | | 1.5 | 90 | 84 | 79 | 75 | 88 | 83 | 78 | 74 | 85 | 80 | 76 | 73 | 82 | 78 | 75 | 72 | 69 |
| | 等価発光面積 | | c m ² | 2.0 | 94 | 89 | 84 | 81 | 92 | 87 | 83 | 80 | 89 | 85 | 81 | 79 | 86 | 82 | 80 | 77 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 96 | 92 | 88 | 85 | 95 | 90 | 87 | 84 | 91 | 88 | 85 | 82 | 88 | 85 | 83 | 80 | 77 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 98 | 94 | 91 | 88 | 96 | 93 | 89 | 87 | 93 | 90 | 87 | 85 | 90 | 87 | 85 | 83 | 79 |
| H m | 0.84 H m | 0.84 H m | 4.0 | 100 | 97 | 94 | 92 | 98 | 95 | 93 | 91 | 95 | 92 | 90 | 88 | 92 | 90 | 88 | 86 | 83 |
| | | | 5.0 | 101 | 99 | 96 | 94 | 100 | 97 | 95 | 93 | 96 | 94 | 92 | 91 | 93 | 91 | 90 | 88 | 85 |
| | | | 7.0 | 103 | 101 | 99 | 97 | 101 | 99 | 98 | 96 | 98 | 96 | 95 | 94 | 94 | 93 | 92 | 91 | 87 |
| | | | 10.0 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99 | 99 | 98 | 97 | 96 | 96 | 95 | 94 | 93 | 89 |

