

屋内照明器具特性

品番 (品名)	NTS64153 + NTS90101 + NTS910	
光源	LED3000_70_1140 ×1 1140.0 lm	
管理番号	K0168007 (1) DJ 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%																																						
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10																																							
上方光束	0%	反射率	照明率 (X0.01)																				ZCM																																		
下方光束	100%	室指数																																																							
保守率	良 0.63	0.6	0.6	76	68	63	59	75	67	63	59	73	67	62	59	72	66	62	59	58	0.8	84	77	72	69	83	76	72	69	81	75	71	68	79	75	71	68	67	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	72	
	中	0.6	1.25	93	88	83	80	92	87	83	80	90	86	82	79	88	84	81	79	77	1.5	96	91	87	84	95	90	87	84	92	89	86	83	90	87	85	83	81	2.0	99	95	92	89	98	94	91	89	96	93	90	88	94	91	89	87	85	
	否 0.56	2.5	101	98	95	93	100	97	94	92	98	95	93	91	96	94	92	90	88	3.0	102	99	97	95	101	99	96	94	99	97	95	93	97	95	94	92	90	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92		
下方投影面積	cm ²	等価発光面積	cm ²	5.0	105	103	101	100	104	102	101	99	101	100	99	98	99	98	97	96	94	7.0	106	105	103	102	105	104	102	101	103	102	101	100	100	100	99	98	96	10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	100	97
				取付高さ	器具間隔最大限																																																				
Hm	0.67Hm	0.67Hm	Hm	3.0	102	99	97	95	101	99	96	94	99	97	95	93	97	95	94	92	90	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92	5.0	105	103	101	100	104	102	101	99	101	100	99	98	99	98	97	96	94
				7.0	106	105	103	102	105	104	102	101	103	102	101	100	100	100	99	98	96	10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	100	97																		

