

屋内照明器具特性

品番 (品名)	NYM20246+NYK00117	
光源	LED5000_85_47620 ×1	47620.0 1 m
管理番号	K0185714(0)DB1	
BZ分類	BZ3	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	98%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	65	55	48	44	64	54	48	44	62	53	48	44	60	52	47	43	41
	中	0.81	0.8	75	65	59	54	73	65	59	54	71	63	58	54	68	62	57	53	51
	否	0.77	1.0	81	72	66	62	79	71	66	61	77	70	65	61	74	68	64	60	58
			1.25	86	78	73	68	84	77	72	68	81	76	71	67	79	74	70	66	64
下方投影面積	c m ²		1.5	89	82	77	73	88	81	77	73	85	79	75	72	82	78	74	71	68
	等価発光面積		c m ²	2.0	94	88	84	80	92	87	83	79	89	85	81	78	86	83	80	77
取付高さ	器具間隔最大限		2.5	96	92	88	84	95	91	87	84	92	88	85	82	89	86	83	81	78
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	97	93	90	87	94	91	88	85	91	88	86	84	81
H m	1.24 H m	1.24 H m	4.0	101	97	95	92	99	96	93	91	96	94	91	89	93	91	89	88	85
			5.0	102	99	97	95	101	98	96	94	98	96	94	92	95	93	92	90	87
			7.0	104	102	100	98	102	100	99	97	99	98	96	95	97	95	94	93	90
			10.0	105	103	102	101	103	102	101	100	101	99	98	97	98	97	96	95	92

