

# 屋内照明器具特性

品番 (品名)	NYM20221+NYK00116	
光源	LED5000_85_15120 ×1	15120.0 1 m
管理番号	K0185726(0)DB1	
BZ分類	BZ2/1.4/BZ3	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		3%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		97%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.83	0.6	66	56	50	45	65	56	49	45	63	54	49	45	61	53	48	45	43	
	中	0.81	0.8	75	66	60	55	74	65	60	55	71	64	59	55	69	63	58	54	52	
	否	0.77	1.0	81	73	67	62	80	72	66	62	77	70	65	61	74	69	64	61	59	
			1.25	86	79	73	69	85	78	72	68	82	76	71	68	79	74	70	67	65	
下方投影面積	c m <sup>2</sup>		1.5	89	83	77	73	88	82	77	73	85	80	75	72	82	78	74	71	69	
	等価発光面積		c m <sup>2</sup>	2.0	94	88	84	80	92	87	83	79	89	85	81	78	86	83	80	77	74
取付高さ	器具間隔最大限		2.5	96	92	88	84	95	90	87	84	92	88	85	82	89	86	83	81	78	
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	97	93	90	87	94	90	88	85	91	88	86	84	81	
H m	1.18 H m	1.18 H m	4.0	101	97	94	92	99	96	93	91	96	93	91	89	93	91	89	87	84	
			5.0	102	99	97	95	100	98	96	94	97	95	93	92	95	93	91	90	87	
			7.0	104	102	100	98	102	100	98	97	99	97	96	95	96	95	94	93	89	
			10.0	105	103	102	101	103	102	101	99	100	99	98	97	97	97	96	95	91	

