

屋内照明器具特性

| | | |
|---------|---------------------|-------------|
| 品番 (品名) | NYM20226+NYK00119 | |
| 光源 | LED5000_85_43840 ×1 | 43840.0 1 m |
| 管理番号 | K0185716(0)DB1 | |
| BZ分類 | BZ3 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 5% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 95% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 | 0.77 | 0.6 | 64 | 54 | 48 | 43 | 63 | 53 | 47 | 43 | 60 | 52 | 46 | 42 | 58 | 51 | 46 | 42 | 40 |
| | | 0.72 | 0.8 | 74 | 64 | 58 | 53 | 72 | 63 | 57 | 53 | 69 | 62 | 56 | 52 | 66 | 60 | 55 | 51 | 49 |
| | | 0.68 | 1.0 | 80 | 71 | 65 | 60 | 78 | 70 | 64 | 60 | 75 | 68 | 63 | 59 | 72 | 66 | 62 | 58 | 56 |
| | | | 1.25 | 85 | 77 | 71 | 67 | 83 | 76 | 70 | 66 | 80 | 74 | 69 | 65 | 77 | 71 | 67 | 64 | 61 |
| 下方投影面積 | c m ² | 1.5 | 88 | 81 | 76 | 71 | 86 | 80 | 75 | 71 | 83 | 77 | 73 | 69 | 80 | 75 | 71 | 68 | 65 | |
| | | 2.0 | 93 | 87 | 82 | 78 | 91 | 85 | 81 | 77 | 87 | 83 | 79 | 76 | 84 | 80 | 77 | 74 | 71 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 95 | 90 | 86 | 83 | 94 | 89 | 85 | 82 | 90 | 86 | 83 | 80 | 87 | 84 | 81 | 78 | 75 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 97 | 93 | 89 | 86 | 95 | 91 | 88 | 85 | 92 | 89 | 86 | 83 | 89 | 86 | 83 | 81 | 78 |
| H m | 1.17 H m | 1.17 H m | 4.0 | 100 | 96 | 93 | 90 | 98 | 95 | 92 | 89 | 94 | 92 | 89 | 87 | 91 | 89 | 87 | 85 | 82 |
| | | | 5.0 | 101 | 98 | 96 | 93 | 99 | 97 | 94 | 92 | 96 | 94 | 92 | 90 | 93 | 91 | 89 | 88 | 84 |
| | | | 7.0 | 103 | 101 | 99 | 97 | 101 | 99 | 97 | 96 | 98 | 96 | 95 | 93 | 94 | 93 | 92 | 91 | 87 |
| | | | 10.0 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 98 | 99 | 98 | 97 | 96 | 96 | 95 | 94 | 93 | 89 |

