

屋内照明器具特性

品番 (品名)	NYM20242 + NYK00118	
光源	LED5000_85_18740 ×1	18740.0 lm
管理番号	K0185724 (0) DB1	
BZ分類	BZ1 / 0.7 / BZ2 / 2.8 / BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	5 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	95 %		室指数	照明率 (X0.01)																ZCM
保守率	良 中 否	0.77	0.6	71	62	56	52	69	61	56	52	67	60	55	52	65	59	54	51	49
		0.72	0.8	78	70	64	60	77	69	64	60	74	68	63	59	72	66	62	59	57
			1.0	83	75	70	66	81	74	69	65	79	73	68	65	76	71	67	64	62
		0.68	1.25	87	80	75	71	86	79	74	71	82	77	73	70	80	75	72	69	66
下方投影面積	c m ²	1.5	90	84	79	75	88	83	78	74	85	80	76	73	82	78	75	72	69	
		2.0	94	89	84	81	92	87	83	80	89	85	81	79	86	82	80	77	74	
取付高さ	器具間隔最大限		2.5	96	92	88	85	95	90	87	84	91	88	85	82	88	85	83	80	77
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	96	93	89	87	93	90	87	85	90	87	85	83	79
H m	0.84 H m	0.84 H m	4.0	100	97	94	92	98	95	93	91	95	92	90	88	92	90	88	86	83
			5.0	101	99	96	94	100	97	95	93	96	94	92	91	93	91	90	88	85
			7.0	103	101	99	97	101	99	98	96	98	96	95	94	94	93	92	91	87
			10.0	104	103	101	100	102	101	100	99	99	98	97	96	96	95	94	93	89

