

# 屋内照明器具特性

品番 (品名)	NYM20246 + NYK00119	
光源	LED5000_85_43840 ×1	43840.0 lm
管理番号	K0185716 (0) DB 1	
BZ分類	BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	95 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良 中 否	0.77	0.6	64	54	48	43	63	53	47	43	60	52	46	42	58	51	46	42	40			
		0.72	0.8	74	64	58	53	72	63	57	53	69	62	56	52	66	60	55	51	49			
			1.0	80	71	65	60	78	70	64	60	75	68	63	59	72	66	62	58	56			
		0.68	1.25	85	77	71	67	83	76	70	66	80	74	69	65	77	71	67	64	61			
下方投影面積	c m <sup>2</sup>	1.5	88	81	76	71	86	80	75	71	83	77	73	69	80	75	71	68	65				
		2.0	93	87	82	78	91	85	81	77	87	83	79	76	84	80	77	74	71				
取付高さ	器具間隔最大限		2.5	95	90	86	83	94	89	85	82	90	86	83	80	87	84	81	78	75			
	横方向 (A)	縦方向 (B)	3.0	97	93	89	86	95	91	88	85	92	89	86	83	89	86	83	81	78			
H m	1.17 H m	1.17 H m	4.0	100	96	93	90	98	95	92	89	94	92	89	87	91	89	87	85	82			
			5.0	101	98	96	93	99	97	94	92	96	94	92	90	93	91	89	88	84			
			7.0	103	101	99	97	101	99	97	96	98	96	95	93	94	93	92	91	87			
			10.0	104	103	101	100	102	101	100	98	99	98	97	96	95	94	93	89				

