

# 屋内照明器具特性

|         |                     |             |
|---------|---------------------|-------------|
| 品番 (品名) | NYM20286+NYK00112   |             |
| 光源      | LED5000_85_44850 ×1 | 44850.0 1 m |
| 管理番号    | K0185715 (0) DB 1   |             |
| BZ分類    | BZ3                 |             |

|        |                  |          |      |      |     |     |      |      |     |     |      |      |    |    |      |      |    |    |     |     |     |
|--------|------------------|----------|------|------|-----|-----|------|------|-----|-----|------|------|----|----|------|------|----|----|-----|-----|-----|
| 器具効率   | 100 %            | 天井       | 80 % |      |     |     | 70 % |      |     |     | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |     |
|        | 上方光束<br>5 %      |          | 反射率  | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |     |
| 下方光束   | 95 %             | 床        |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |     |
| 室指数    | 照明率 ( X0.01 )    |          |      |      |     |     |      |      |     |     |      |      |    |    |      |      |    |    |     |     | ZCM |
| 保守率    | 良<br>中<br>否      | 0.77     | 0.6  | 65   | 55  | 48  | 44   | 64   | 54  | 48  | 44   | 61   | 53 | 47 | 43   | 59   | 52 | 46 | 43  | 41  |     |
|        |                  | 0.72     | 0.8  | 74   | 65  | 58  | 54   | 73   | 64  | 58  | 54   | 70   | 62 | 57 | 53   | 67   | 61 | 56 | 52  | 50  |     |
|        |                  | 0.68     | 1.0  | 80   | 72  | 65  | 61   | 78   | 71  | 65  | 60   | 75   | 69 | 64 | 60   | 73   | 67 | 62 | 59  | 56  |     |
|        |                  |          | 1.25 | 85   | 77  | 72  | 67   | 83   | 76  | 71  | 67   | 80   | 74 | 70 | 66   | 77   | 72 | 68 | 65  | 62  |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 88   | 82   | 76  | 72  | 87   | 80   | 75  | 71  | 83   | 78   | 74 | 70 | 80   | 76   | 72 | 69 | 66  |     |     |
|        |                  | 2.0      | 93   | 87   | 83  | 79  | 91   | 86   | 82  | 78  | 88   | 83   | 80 | 76 | 85   | 81   | 78 | 75 | 72  |     |     |
| 取付高さ   | 器具間隔最大限          |          | 2.5  | 96   | 91  | 87  | 83   | 94   | 89  | 86  | 82   | 90   | 87 | 83 | 81   | 87   | 84 | 81 | 79  | 76  |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0  | 98   | 93  | 90  | 86   | 96   | 92  | 89  | 86   | 92   | 89 | 86 | 84   | 89   | 86 | 84 | 82  | 79  |     |
| H m    | 1.16 H m         | 1.16 H m | 4.0  | 100  | 97  | 94  | 91   | 98   | 95  | 92  | 90   | 95   | 92 | 90 | 88   | 91   | 89 | 87 | 86  | 82  |     |
|        |                  |          | 5.0  | 101  | 99  | 96  | 94   | 100  | 97  | 95  | 93   | 96   | 94 | 92 | 90   | 93   | 91 | 90 | 88  | 84  |     |
|        |                  |          | 7.0  | 103  | 101 | 99  | 97   | 101  | 99  | 98  | 96   | 98   | 96 | 95 | 93   | 95   | 93 | 92 | 91  | 87  |     |
|        |                  |          | 10.0 | 104  | 103 | 101 | 100  | 103  | 101 | 100 | 99   | 99   | 98 | 97 | 96   | 96   | 95 | 94 | 93  | 89  |     |

