

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND3591SW                    |  |  |  |  |  |  |  |  |  |
| 光源      | LED4000_80_4045 x1 4045.0 1m |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0160788(0)DB1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ2/0.9/BZ1/4.5/BZ2/6.0/BZ1  |  |  |  |  |  |  |  |  |  |

|        |                   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |
|--------|-------------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|
| 器具効率   | 100%              | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |    |    |
|        | 上方光束              |         | 0%   | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 0% |
|        | 下方光束              |         | 100% |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    |
| 室指数    | 照明率 ( X0.01 ) ZCM |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |
| 保守率    | 良                 | 0.76    | 0.6  | 69  | 60  | 54  | 50  | 68  | 59  | 54  | 50  | 66  | 59  | 53  | 50  | 65  | 58  | 53  | 49 | 48 |    |
|        | 中                 | 0.72    | 0.8  | 79  | 71  | 66  | 62  | 78  | 71  | 65  | 62  | 76  | 70  | 65  | 61  | 74  | 69  | 64  | 61 | 59 |    |
|        | 否                 | 0.64    | 1.0  | 86  | 78  | 73  | 69  | 84  | 78  | 73  | 69  | 82  | 77  | 72  | 69  | 80  | 75  | 72  | 69 | 67 |    |
|        |                   |         | 1.25 | 90  | 84  | 80  | 76  | 89  | 84  | 79  | 76  | 87  | 82  | 78  | 75  | 85  | 81  | 78  | 75 | 73 |    |
| 下方投影面積 |                   |         | 1.5  | 93  | 88  | 84  | 80  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 79  | 88  | 84  | 81  | 79 | 77 |    |
|        |                   |         | 2.0  | 97  | 93  | 89  | 86  | 96  | 92  | 89  | 86  | 94  | 90  | 88  | 85  | 92  | 89  | 86  | 84 | 82 |    |
| 取付高さ   | 器具間隔最大限           |         | 2.5  | 100 | 96  | 93  | 90  | 98  | 95  | 92  | 90  | 96  | 93  | 91  | 89  | 94  | 92  | 90  | 88 | 86 |    |
|        | 横方向 (A)           | 縦方向 (B) | 3.0  | 101 | 98  | 95  | 93  | 100 | 97  | 95  | 92  | 98  | 95  | 93  | 91  | 95  | 93  | 92  | 90 | 88 |    |
| Hm     | 1.36Hm            | 1.36Hm  | 4.0  | 103 | 101 | 98  | 96  | 102 | 100 | 98  | 96  | 99  | 98  | 96  | 94  | 97  | 96  | 94  | 93 | 91 |    |
|        |                   |         | 5.0  | 104 | 102 | 100 | 99  | 103 | 101 | 99  | 98  | 101 | 99  | 98  | 96  | 98  | 97  | 96  | 95 | 92 |    |
|        |                   |         | 7.0  | 105 | 104 | 102 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97 | 94 |    |
|        |                   |         | 10.0 | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 99 | 96 |    |

