

屋内照明器具特性

品番(品名)	NYY71060+NTS90150	
光源	LED3500_70_595 x1	595.0 lm
管理番号	K0152450(*)DJ1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		下方光束 102%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
反射率		壁	10%				10%				10%				10%				0%	
室指数		床	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	1.01	0.99	0.97	0.96	1.01	0.99	0.97	0.96	1.00	0.98	0.97	0.96	1.00	0.98	0.97	0.96	0.95
	中	0.63	0.8	1.03	1.01	0.99	0.98	1.03	1.01	0.99	0.98	1.02	1.00	0.99	0.98	1.01	0.99	0.98	0.97	0.97
	否	0.56	1.0	1.04	1.02	1.01	1.00	1.04	1.02	1.00	0.99	1.03	1.01	1.00	0.99	1.02	1.00	0.99	0.99	0.98
下方投影面積	等価発光面積	cm ²	1.25	1.05	1.03	1.02	1.01	1.05	1.03	1.02	1.01	1.04	1.02	1.01	1.00	1.01	1.00	1.00	0.99	0.98
			1.5	1.06	1.04	1.03	1.02	1.05	1.04	1.02	1.01	1.04	1.03	1.02	1.01	1.03	1.02	1.01	1.00	0.99
取付高さ	器具間隔最大限		2.0	1.07	1.06	1.04	1.03	1.06	1.05	1.04	1.03	1.05	1.04	1.03	1.02	1.03	1.02	1.01	1.00	1.00
	横方向(A)	縦方向(B)	2.5	1.08	1.06	1.05	1.04	1.07	1.06	1.05	1.04	1.05	1.04	1.03	1.03	1.04	1.03	1.02	1.01	1.00
Hm	0.28Hm	0.28Hm	3.0	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.05	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.00
			4.0	1.09	1.08	1.07	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.03	1.00
			5.0	1.09	1.08	1.07	1.07	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.01
			7.0	1.09	1.09	1.08	1.08	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.01
			10.0	1.10	1.09	1.09	1.08	1.08	1.08	1.08	1.07	1.06	1.06	1.06	1.06	1.04	1.04	1.04	1.04	1.01

