

# 屋内照明器具特性

品番(品名)	NYY75023+NTS90150		
光源	LED3000_70_350 x1	350.0 lm	
管理番号	K0152454(7)DJ1		
BZ分類	BZ1		

器具効率	102%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		下方光束 102%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
反射率		壁	10%				10%				10%				10%				0%				
室指数		床	照明率 ( X0.01 )																ZCM				
保守率	良 0.67	中 0.63	否 0.56	0.6	1.01	0.99	0.97	0.96	1.01	0.99	0.97	0.96	1.00	0.98	0.97	0.96	1.00	0.98	0.97	0.96	0.95		
	1.0			1.04	1.02	1.01	0.99	1.04	1.02	1.00	0.99	1.03	1.01	1.00	0.99	1.02	1.00	0.99	0.98	0.97	0.97		
	1.25			1.05	1.03	1.02	1.01	1.05	1.03	1.02	1.00	0.99	1.03	1.02	1.01	1.00	1.01	1.00	0.99	0.99	0.98	0.98	
下方投影面積	cm <sup>2</sup>	1.5	1.06	1.04	1.03	1.02	1.05	1.04	1.02	1.01	1.04	1.03	1.02	1.01	1.03	1.02	1.01	1.00	0.99	0.99			
		2.0	1.07	1.05	1.04	1.03	1.06	1.05	1.04	1.03	1.05	1.03	1.03	1.02	1.03	1.02	1.01	1.01	1.00	0.99	0.99		
取付高さ	器具間隔最大限		Hm	0.28Hm	0.28Hm	2.5	1.07	1.06	1.05	1.04	1.07	1.05	1.04	1.04	1.05	1.04	1.03	1.02	1.03	1.03	1.02	1.01	1.00
	横方向(A)	縦方向(B)				3.0	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.05	1.04	1.04	1.03	1.04	1.03	1.02	1.02	1.01
Hm	0.28Hm	0.28Hm	4.0	1.08	1.07	1.07	1.06	1.07	1.07	1.06	1.05	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.03	1.02	1.01	1.00	
			5.0	1.09	1.08	1.07	1.07	1.08	1.07	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.03	1.02	1.01	1.00
			7.0	1.09	1.08	1.08	1.07	1.08	1.07	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.03	1.02	1.01	1.00
10.0	1.09	1.09	1.09	1.08	1.08	1.08	1.08	1.07	1.06	1.06	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.03	1.02	1.01	1.00		

