

屋内照明器具特性

品番(品名)	NYY75023+NTS90100	
光源	LED3000_70_225 x1	225.0 lm
管理番号	K0152454(7)DJ1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%																																		
	上方光束 0%		下方光束 102%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
反射率		壁	10%				10%				10%				10%				0%																																		
室指数		床	照明率 (X0.01)																ZCM																																		
保守率	良 0.67	中 0.63	否 0.56	0.6	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	0.6	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	0.6	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	0.6	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	0.6	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
	1.25			1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0						
	2.5			3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0									
下方投影面積	cm ²	器具間隔最大限																																																			
等価発光面積	cm ²	高さ	横方向(A)	縦方向(B)																																																	
		Hm	0.28Hm	0.28Hm																																																	

