

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | NYY75040 + NTS90150 |           |
| 光源      | LED3500_70_805 ×1   | 805.0 l m |
| 管理番号    | K0152456 (* ) DJ 1  |           |
| BZ分類    | BZ1                 |           |

| 器具効率   | 100 %            | 天井       | 80 %          |      |     |     | 70 % |      |     |     | 50 % |      |     |     | 30 % |      |     |     | 0 % |     |
|--------|------------------|----------|---------------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|
|        |                  |          | 70            | 50   | 30  | 10  | 70   | 50   | 30  | 10  | 70   | 50   | 30  | 10  | 70   | 50   | 30  | 10  |     |     |
| 上方光束   | 0 %              | 反射率      | 10 %          |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 0 % |     |
| 下方光束   | 100 %            |          | 壁             | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |     | 0 % |
|        |                  | 床        | 10 %          |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 0 % |     |
|        |                  | 室指数      | 照明率 ( X0.01 ) |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     | ZCM |     |
| 保守率    | 良 0.67           | 0.6      | 83            | 77   | 73  | 70  | 82   | 76   | 72  | 70  | 81   | 76   | 72  | 69  | 80   | 75   | 72  | 69  | 68  |     |
|        | 中 0.63           | 0.8      | 90            | 84   | 80  | 78  | 89   | 84   | 80  | 77  | 87   | 83   | 80  | 77  | 86   | 82   | 79  | 77  | 76  |     |
|        | 否 0.56           | 1.0      | 94            | 89   | 85  | 82  | 93   | 88   | 85  | 82  | 91   | 87   | 84  | 82  | 89   | 86   | 84  | 82  | 80  |     |
| 下方投影面積 | c m <sup>2</sup> | 1.25     | 97            | 92   | 89  | 87  | 96   | 92   | 89  | 86  | 94   | 91   | 88  | 86  | 92   | 90   | 87  | 85  | 84  |     |
|        |                  | 1.5      | 99            | 95   | 92  | 90  | 98   | 94   | 92  | 89  | 96   | 93   | 91  | 89  | 94   | 92   | 90  | 88  | 87  |     |
| 等価発光面積 | c m <sup>2</sup> | 2.0      | 101           | 98   | 96  | 94  | 100  | 98   | 95  | 93  | 98   | 96   | 94  | 92  | 97   | 95   | 93  | 92  | 90  |     |
|        |                  | 2.5      | 103           | 100  | 98  | 96  | 102  | 99   | 97  | 96  | 100  | 98   | 96  | 95  | 98   | 96   | 95  | 94  | 92  |     |
| 取付高さ   | 器具間隔最大限          |          | 3.0           | 104  | 102 | 100 | 98   | 103  | 101 | 99  | 97   | 101  | 99  | 98  | 96   | 99   | 97  | 96  | 95  | 93  |
|        | 横方向 (A)          | 縦方向 (B)  | 4.0           | 105  | 103 | 102 | 100  | 104  | 102 | 101 | 100  | 102  | 101 | 99  | 98   | 100  | 99  | 98  | 97  | 95  |
| H m    | 0.64 H m         | 0.64 H m | 5.0           | 106  | 104 | 103 | 102  | 105  | 103 | 102 | 101  | 103  | 102 | 101 | 100  | 101  | 100 | 99  | 98  | 96  |
|        |                  |          | 7.0           | 107  | 106 | 105 | 104  | 106  | 105 | 104 | 103  | 103  | 103 | 102 | 101  | 101  | 101 | 100 | 100 | 97  |
|        |                  |          | 10.0          | 107  | 107 | 106 | 105  | 106  | 105 | 104 | 104  | 103  | 103 | 102 | 102  | 101  | 101 | 101 | 98  |     |

