

# 屋内照明器具特性

|         |                          |           |
|---------|--------------------------|-----------|
| 品番 (品名) | NYY65940+NYY91300S+NTS90 |           |
| 光源      | LED5000_70_1880 ×1       | 1880.0 lm |
| 管理番号    | K0164960(9)DJ1           |           |
| BZ分類    | BZ1                      |           |

| 器具効率             | 100%            | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|------------------|-----------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|                  |                 |         | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束             | 0%              | 反射率     | 壁             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束             | 100%            |         | 床             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|                  |                 | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率              | 良 0.67          | 0.6     | 92            | 88  | 85  | 83  | 91  | 87  | 85  | 83  | 90  | 87  | 85  | 83  | 89  | 86  | 84  | 83  | 82  |    |
|                  | 中 0.63          | 0.8     | 96            | 92  | 90  | 88  | 95  | 92  | 89  | 88  | 94  | 91  | 89  | 87  | 93  | 91  | 89  | 87  | 86  |    |
|                  | 否 0.56          | 1.0     | 99            | 95  | 93  | 91  | 98  | 95  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 90  | 89  |    |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 101           | 98  | 95  | 94  | 100 | 97  | 95  | 93  | 98  | 96  | 94  | 93  | 97  | 95  | 94  | 92  | 91  |    |
|                  |                 | 1.5     | 102           | 99  | 97  | 95  | 101 | 99  | 97  | 95  | 100 | 97  | 96  | 95  | 98  | 96  | 95  | 94  | 93  |    |
|                  |                 | 2.0     | 104           | 101 | 100 | 98  | 103 | 101 | 99  | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 97  | 96  | 94  |    |
| 取付高さ             | 器具間隔最大限         |         | 2.5           | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 102 | 100 | 99  | 100 | 99  | 98  | 97  | 95  |    |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0           | 105 | 104 | 102 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 101 | 100 | 99  | 96  |    |
| Hm               | 0.77Hm          | 0.77Hm  | 4.0           | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 99  | 97  |    |
|                  |                 |         | 5.0           | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 102 | 101 | 100 | 98  |    |
|                  |                 |         | 7.0           | 107 | 106 | 106 | 105 | 106 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 102 | 101 | 101 | 98  |    |
|                  |                 |         | 10.0          | 108 | 107 | 106 | 106 | 106 | 105 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 102 | 101 | 99  |    |

