

屋内照明器具特性	
品番 (品名)	PA07520WWWP40+NTS90200
光源	LED4000_70_220 ×1                      220.0 l m
管理番号	K0156452 ( 2 ) DB 1
BZ分類	BZ1

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	1 %	反射率	壁																	
下方光束	99 %		床	10 %				10 %				10 %				10 %				
		室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.63	0.6	72	63	57	53	70	62	57	53	69	61	56	53	67	60	56	53	51
	中	0.6	0.8	80	73	67	63	79	72	67	63	77	71	66	63	75	70	66	63	61
	否	0.56	1.0	86	79	74	70	85	78	73	70	82	77	73	69	80	76	72	69	67
下方投影面積	cm <sup>2</sup>	1.25	90	84	80	76	89	83	79	76	87	82	78	75	85	81	77	75	73	
		1.5	93	88	84	81	92	87	83	80	90	86	82	79	88	84	81	79	77	
等価発光面積	cm <sup>2</sup>	2.0	97	93	89	86	96	92	89	86	93	90	87	85	91	88	86	84	82	
		2.5	99	96	93	90	98	95	92	90	96	93	90	88	93	91	89	87	85	
取付高さ	器具間隔最大限		3.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	90	87
	横方向 ( A )	縦方向 ( B )	4.0	103	100	98	96	101	99	97	95	99	97	95	94	97	95	94	92	90
H m	0.65 H m	0.85 H m	5.0	104	102	100	98	102	101	99	97	100	98	97	96	98	96	95	94	92
			7.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93
			10.0	106	105	104	103	105	104	103	102	102	101	101	100	100	99	98	98	95

