

屋内照明器具特性

品番 (品名)	PA10035WWWP40+NTS90250		
光源	LED4000_70_1025 ×1	1025.0 lm	
管理番号	K0153569(4)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	100%	床	10%				10%				10%				10%				0%					
室指数	照明率 (X0.01)																			ZCM				
保守率	良	0.63	0.6	0.56	0.6	76	68	63	60	75	68	63	60	74	67	63	60	72	66	62	59	58		
	中	0.6	0.6	0.6	0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67		
	否	0.56	0.56	0.56	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	73		
下方投影面積	等価発光面積	cm ²	cm ²	1.25	93	88	83	80	92	87	83	80	90	86	82	80	88	84	81	79	77	77		
				1.5	96	91	87	84	94	90	87	84	92	89	86	83	90	87	85	83	81	81	81	
取付高さ	器具間隔最大限		Hm	0.49Hm	0.95Hm	2.5	101	98	95	93	100	97	94	92	97	95	93	91	95	93	92	90	88	
	横方向 (A)	縦方向 (B)				3.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90	90
Hm	Hm	Hm	Hm	Hm	Hm	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92	92
						5.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	99	98	97	96
Hm	Hm	Hm	Hm	Hm	Hm	7.0	106	104	103	102	105	103	102	101	102	101	100	100	100	99	99	98	95	95
						10.0	107	106	105	104	105	105	104	103	103	102	102	101	101	100	100	99	99	97

