

屋内照明器具特性

品番 (品名)	PA12545 WWWP40 + NTS90250		
光源	LED4000_70_1740 ×1	1740.0 lm	
管理番号	K0153569 (4) DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁		床		10%		10%		10%		10%		10%		0%			
下方光束	100%		室指数		照明率 (X0.01)															
保守率	良 0.63	0.6	0.6	76	68	63	60	75	68	63	60	74	67	63	60	72	66	62	59	58
	中 0.6	0.6	0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67
	否 0.56	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	73	73
下方投影面積	cm ²	1.25	93	88	83	80	92	87	83	80	90	86	82	80	88	84	81	79	77	77
		1.5	96	91	87	84	94	90	87	84	92	89	86	83	90	87	85	83	81	81
等価発光面積	cm ²	2.0	99	95	92	89	98	94	91	89	96	93	90	88	94	91	89	87	85	85
		2.5	101	98	95	93	100	97	94	92	97	95	93	91	95	93	92	90	88	88
取付高さ	器具間隔最大限		3.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90
	横方向 (A)	縦方向 (B)	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92
Hm	0.49Hm	0.95Hm	5.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94
			7.0	106	104	103	102	105	103	102	101	102	101	100	100	99	99	98	95	95
			10.0	107	106	105	104	105	104	103	103	102	102	101	101	100	100	99	97	97

