

屋内照明器具特性	
品番 (品名)	PA81003UPM35
光源	LED3500_70_685 ×1 685.0 lm
管理番号	K0167033(0)DB1
BZ分類	BZ10

器具効率	100%	天井	80%				70%				50%				30%				0%
	上方光束		100%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	0%	床	10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																
保守率	良 0.69	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0
	中 0.67	0.8	51	41	34	29	43	35	30	25	29	24	21	18	17	14	12	11	0
	否 0.63	1.0	56	47	40	35	48	41	35	31	33	28	24	22	19	16	14	13	0
下方投影面積 等価発光面積	cm ²	1.25	61	53	47	42	52	46	40	36	36	31	28	26	20	18	16	15	0
		1.5	65	57	51	47	56	49	44	40	38	34	31	29	22	20	18	17	0
		2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	63	65	61	57	54	44	42	40	38	26	24	23	0
1.5m	0.3m	0.3m	4.0	78	74	71	68	67	64	61	59	46	44	43	41	27	26	25	0
2	0.4	0.4	5.0	80	76	73	71	69	66	64	61	47	46	44	43	27	27	26	0
2.5	0.5	0.5	7.0	82	79	77	75	70	68	67	65	49	48	46	45	28	28	27	0
3	0.6	0.6	10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	29	28	0

