

屋内照明器具特性	
品番 (品名)	PTSR10027KVW(1TOUBUN)
光源	LED2700_70_66 x1 66.0 l m
管理番号	K0155124(0)DY1
BZ分類	BZ6

器具効率	99%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	5.2	3.9	3.1	2.5	5.0	3.8	3.0	2.5	4.7	3.7	2.9	2.4	4.5	3.5	2.9	2.4	2.2
	中	0.67	0.8	6.1	4.9	4.0	3.4	6.0	4.8	4.0	3.4	5.6	4.6	3.9	3.3	5.3	4.4	3.8	3.3	3.0
	否	0.63	1.0	6.8	5.6	4.7	4.1	6.6	5.5	4.7	4.0	6.2	5.2	4.5	4.0	5.9	5.0	4.4	3.9	3.6
			1.25	7.4	6.3	5.4	4.8	7.2	6.1	5.3	4.7	6.8	5.9	5.2	4.6	6.4	5.7	5.1	4.6	4.3
下方投影面積		cm ²	1.5	7.8	6.8	6.0	5.3	7.6	6.6	5.9	5.3	7.2	6.4	5.7	5.2	6.8	6.1	5.6	5.1	4.8
等価発光面積		cm ²	2.0	8.4	7.5	6.8	6.2	8.2	7.3	6.7	6.1	7.8	7.1	6.5	6.0	7.4	6.8	6.3	5.9	5.5
取付高さ	器具間隔最大限		2.5	8.8	8.0	7.3	6.8	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.5	7.8	7.3	6.8	6.4	6.1
	横方向 (A)	縦方向 (B)	3.0	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.1	8.4	7.9	7.4	7.0	8.1	7.6	7.2	6.8	6.5
Hm	1.32Hm	1.32Hm	4.0	9.4	8.8	8.3	7.9	9.2	8.7	8.2	7.8	8.8	8.4	8.0	7.6	8.4	8.1	7.7	7.4	7.0
			5.0	9.6	9.1	8.7	8.3	9.4	9.0	8.6	8.2	9.0	8.7	8.3	8.0	8.7	8.4	8.1	7.8	7.4
			7.0	9.9	9.5	9.2	8.8	9.7	9.4	9.0	8.7	9.3	9.0	8.8	8.5	9.0	8.7	8.5	8.3	7.9
			10.0	10.1	9.8	9.6	9.3	9.9	9.7	9.4	9.2	9.6	9.3	9.1	8.9	9.2	9.0	8.9	8.7	8.3

