

# 屋内照明器具特性

品番 (品名)	PTSR10030KSP (1TOUBUN)														
光源	LED3000_70_68 x1 68.0 l m														
管理番号	K0155128 (0) DY 1														
BZ分類	BZ2/0.9/BZ3/2.3/BZ4/4.5/BZ5														

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	7 %																			
下方光束	84 %																			
室指数	照明率 ( X0.01) ZCM																			
保守率	良 0.69 中 0.67 否 0.63	0.6	60	51	45	41	58	50	45	41	56	49	44	40	54	47	43	40	38	
		0.8	67	59	53	49	66	58	53	49	63	56	51	48	60	55	50	47	45	
		1.0	72	64	59	54	70	63	58	54	67	61	57	53	64	59	55	52	50	
		1.25	76	69	64	59	74	68	63	59	71	66	61	58	68	63	60	57	54	
下方投影面積	c m <sup>2</sup>	1.5	79	72	67	63	77	71	66	62	74	68	64	61	70	66	63	60	57	
		2.0	83	77	72	68	81	75	71	68	77	73	69	66	74	70	67	64	61	
取付高さ	器具間隔最大限		2.5	85	80	76	72	83	78	74	71	79	75	72	69	76	73	70	67	64
	横方向 (A)	縦方向 (B)	3.0	86	82	78	75	85	80	77	74	81	77	74	72	77	75	72	70	66
H m	1.34 H m	0.38 H m	4.0	89	85	82	79	87	83	80	78	83	80	78	75	79	77	75	73	69
			5.0	90	87	84	81	88	85	82	80	84	82	80	78	81	79	77	75	71
			7.0	92	89	87	85	90	87	85	83	86	84	82	81	82	81	79	78	74
			10.0	93	91	89	88	91	89	88	86	87	86	85	83	84	83	82	80	76

